

CERTIFICATE OF ANALYSIS: PORT MANATEE, FL (Zonguldak, Turkey)

ASTM: FLY ASH, CLASS F (FA-54)



		ANALYSIS OF:	Oct-2023
ASTM C618 & AASHTO M295 REQUIREMENTS	LIMITS ASTM (AASHTO)	RESULTS	TEST METHOD
Fineness; Retained when wet-sieved 45 µm (No. 325) Sieve, max. %	34	29	ASTM C311
Strength Activity Index			
7 day; min. percent of control	75 [†]	94	ASTM C311
28 day, min. percent of control	75 [†]	88	ASTM C311
Water Requirement; max. percent of control	105	100	ASTM C311
Soundness, autoclave expansion, max. %	--	--	ASTM C311
Density, specific gravity (g/cm ³)	--	2.15	ASTM C311
Density; max. variation from average, %	5	NA	ASTM C311
Fineness, max. variaton from average, %	5	NA	ASTM C311

Sum of SiO ₂ , Al ₂ O ₃ , and Fe ₂ O ₃ , min. %	50.0	86.5	ASTM C311
Sulphur Trioxide (SO ₃), max. %	5.0	0.6	ASTM C311
Moisture content, max. %	3.0	0.1	ASTM C311
Loss on ignition, max, %	6.0	1.9	ASTM C311
Silica Oxide (SiO ₂) (%)	--	54.9	ASTM C311
Alumina Oxide (Al ₂ O ₃) (%)	--	25.8	ASTM C311
Iron Oxide (Fe ₂ O ₃) (%)	--	5.7	ASTM C311
Calcium Oxide (CaO) (%)	C > 18.0/F 18.0 max	3.0	ASTM C311
Magnesium Oxide (MgO) (%)	--	2.2	ASTM C311
Sodium Oxide (Na ₂ O) (%)	--	1.1	ASTM C311
Potassium Oxide (K ₂ O) (%)	--	2.5	ASTM C311
Total alkalis (Na ₂ O) eq. = Na ₂ O + 0.658 K ₂ O (%)	--	2.7	ASTM C311
Available alkalis, Na ₂ O eq., (%)	‡	--	ASTM C311

COMMENTS:

Parameters with no limit listed are included for information purposes only, and are not requirements of the standards.

† Meeting the 7 day or the 28 day strength activity index indicates compliance with the specification.

‡ Not a requirement of ASTM C618 or AASHTO M295. Required only when requested by purchaser to limit alkali content in concrete containing reactive aggregate.

This certifies compliance with the most current editions of ASTM C 618 and AASTHO M 295 standards.

REPORT PREPARED BY:	PRINT DATE:
Xiuping Feng - Tech Center Lab Manager 	10/30/2023
Tests performed by Ash Grove Cement - Technical Center	